

KARYA Dijital

TRU JET

DTF FE

- Soft touch
- Flexible
- Vivid color
- Unlimited color opportunity
- Instant proofing



İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.
No: 22 Merter - Güngören / İstanbul - Turkey
P +90 212 637 03 34

BURSA

Anadolu Mh. Karlıdağ Sk. No: 37
Yıldırım - Bursa - Turkey
P +90 224 364 61 40

www.karyadijital.com

satis@karyadijital.com

[f](#) [t](#) [@](#) [v](#) [in](#) /karyadijital

TRU JET

HPFE

TECHNICAL PARAMETERS

Maximum Printing Width	600 mm
Print Head	Two heads EPSON 4720 print head One head for color ink, one head for CMYK
Printing Method	White layer over colored layer
Ink	Pigment ink for PET film
Print Speed	3 Pass - 20m ² / h
RIP Software	TexPrint, Neostampa, MainTop
Printer Equipment	Recirculation pump for white ink
Powdering Equipment	Powder shake control powder and amount control
Drying Equipment	Front heat plate, dry fixation, cold fans
Environment	Temperature :20-30°C Humidity :45% - 65%
Power Specifications	Printer :230W Powdering Machine :1kW - 2,5kW 3 Phase 380 v, 50 Hz
Product Dimensions <small>(WxDxH)</small>	Printer :1660 x 830 x 1570 cm Accessories :1985 x 1090 x 1080 cm
Net / Gross Weight	Printer 152 kg / 180 kg Powdering Machine 180 kg / 260 kg

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.
No: 22 Merter - Güngören / İstanbul - Turkey
P +90 212 637 03 34

BURSA

Anadolu Mh. Karlıdağ Sk. No: 37
Yıldırım - Bursa - Turkey
P +90 224 364 61 40

www.karyadijital.com

     /karyadijital