

DTF FS

- Soft touch
- Flexible
- Vivid color
- Unlimited color opportunity
- Instant proofing



İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.
No: 22 Merter - Güngören / İstanbul - Turkey
P +90 212 637 03 34

BURSA

Anadolu Mh. Karlıdağ Sk. No: 37
Yıldırım - Bursa - Turkey
P +90 224 364 61 40

www.trujet.eu

sales@trujet.eu

[f](#) [@](#) [v](#) [in](#) /trujet

FFS

TECHNICAL PARAMETERS

Maximum Printing Width	600 mm
Print Head	Five heads EPSON i3200 print head Two heads for white color ink, three heads for CMYK
Printing Method	White layer over colored layer
Ink	Pigment ink for PET film
Print Speed	3 Pass - 50m ² / h 6 Pass - 25m ² / h
RIP Software	TexPrint, Neostampa, MainTop
Printer Equipment	Recirculation pump for white ink
Powdering Equipment	Powder shake control powder and amount control
Drying Equipment	Front heat plate, dry fixation, cold fans
Environment	Temperature :20-30°C Humidity :45% - 65%
Power Specifications	Printer :800W Powdering Machine :11.5kW
Product Dimensions (WxDxH)	Printer :1670 x 815 x 1600 mm Accessories :2080 x 980 x 1120 mm
Net / Gross Weight	Printer 150 kg / 210 kg Powdering Machine 370 kg / 430 kg

İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.
No: 22 Merter - Güngören / İstanbul - Turkey
P +90 212 637 03 34

BURSA

Anadolu Mh. Karlıdağ Sk. No: 37
Yıldırım - Bursa - Turkey
P +90 224 364 61 40

www.trujet.eu

sales@trujet.eu

    /trujet